



Taiga Treated Wood Products

Taiga treated wood products are preserved with the trusted Wolman® NB brand of copper azole from Lonza Wood Protection and are tough enough to stand up to termites and fungal decay and versatile enough to be used in all types of natural environments. They can be used in above ground, ground contact and fresh water applications.



**ABOVE
GROUND**



**GROUND
CONTACT**



**FRESH
WATER**



Decades of Proven Performance

- Protects against termites and fungal decay.
- Proven in multiple species including Spruce Pine Fir (SPF), Douglas Fir, SYP, Larch, Hem/Fir, Ponderosa Pine, and more.
- Made with real wood — a renewable, naturally beautiful resource that is harvested in an appropriate, responsible manner.
- Ideal for decking, railing, structural deck components, playgrounds and other backyard projects.
- Versatile to use in fencing and other landscaping applications.
- More economical than alternatives such as cedar, hardwoods, and plastic composites.
- Limited lifetime warranty.



Available with Tanatone® Colour Technology

- Attractive, rich brown tone slowly weathers to warm honey brown then to natural silver grey.
- Eliminates need for initial staining, making your project beautiful for immediate enjoyment.
- Colour technology from Europe specially formulated for Canadian wood species.
- Colourant is added during the pressure treatment process, ensuring protection and initial pre-coloured appearance in one step.
- Initial variation in colour may occur as a result of the natural characteristics of wood. Any variation will blend with exposure.
- Matches your backyard projects without the need for initial staining.

Building Tips

- Check the lumber end-tag. Make sure that the intended use shown on the tag matches your application.
- For 2" lumber, use 3 1/4" nails or 3" screws. For 5/4 decking, use 3" nails or 2 1/2" screws.

Recommended Hardware

Hot-dipped galvanized fasteners (meeting ASTM A 153) and connectors (ASTM A 653 Class G185), or better, are recommended for protection against the effects of moisture often present where treated wood is used. For Permanent Wood Foundations, use 304 or 316 stainless steel. Aluminum should not be used in direct contact with this wood.

Maintenance Tips

- No maintenance is needed to renew resistance to fungi and termites. Wolmanized® wood has a lifetime limited warranty against these organisms. Warranty terms and conditions are available at www.wolmanizedwood.com/warranty.
- Taiga Select with Wolman® NB copper azole naturally weathers to silver grey. Taiga Select with Tanatone® colour technology slowly weathers to a warm honey brown and then to natural silver grey. This weathering process does not indicate any loss of preservative protection. The Tanatone® colour can be refreshed with a suitable brush-on product.
- To help maintain a beautiful appearance, apply water repellent and/or sealer every other year.
- Cross cuts should be treated with an appropriate commercially available end cut preservative (such as copper naphthenate) in order to not void the warranty. See warranty for further details.